


DCC44 SERIES(MALE - FEMALE SWIVEL JIC 37° FLARE 45° ELBOW)


LET



PART NUMBER	Products Description									
	Thread UNF	Nut Hex		Overall Length		Drop		Nipple Hex		Thread UNF
		MM	Inch	MM	Inch	MM	Inch	MM	Inch	
	A	B		C		D		E		F
DCC44-07-07	7/16-20	14.3	0.56	40.7	1.60	10.0	0.39	14.3	0.56	7/16-20
DCC44-09-09	9/16-18	17.5	0.69	43.5	1.71	11.0	0.43	15.9	0.62	9/16-18
DCC44-12-12	3/4-16	22.2	0.87	52.9	2.08	15.0	0.59	20.6	0.81	3/4-16
DCC44-14-14	7/8-14	25.4	1.00	60.2	2.37	16.0	0.63	23.8	0.94	7/8-14
DCC44-17-17	1-1/16-12	31.8	1.25	77.6	3.06	27.0	1.06	28.6	1.12	1-1/16-12
DCC44-21-21	1-5/16-12	38.1	1.50	90.5	3.56	33.0	1.30	35.0	1.38	1-5/16-12
DCC44-26-26	1-5/8-12	50.0	1.97	116.7	4.59	45.0	1.77	42.9	1.69	1-5/8-12

DCC94 SERIES(MALE - FEMALE SWIVEL JIC 37° FLARE 90° ELBOW)

LET



PART NUMBER	Products Description									
	Thread UNF	Nut Hex		Overall Length		Drop		Nipple Hex		Thread UNF
		MM	Inch	MM	Inch	MM	Inch	MM	Inch	
	A	B		C		D		E		F
DCC94-07-07	7/16-20	14.3	0.56	33.0	1.30	46.0	1.81	14.3	0.56	7/16-20
DCC94-07-07S	7/16-20	14.3	0.56	36.0	1.42	21.0	0.83	14.3	0.56	7/16-20
DCC94-09-09	9/16-18	17.5	0.69	37.1	1.46	55.0	2.17	15.9	0.62	9/16-18
DCC94-09-09D39.3	9/16-18	17.5	0.69	40.1	1.58	39.3	1.55	15.9	0.62	9/16-18
DCC94-09-09S	9/16-18	17.5	0.69	40.1	1.58	24.0	0.94	15.9	0.62	9/16-18
DCC94-12-12	3/4-16	22.2	0.87	43.7	1.72	62.0	2.44	20.6	0.81	3/4-16
DCC94-12-12D47.5	3/4-16	22.2	0.87	43.7	1.72	47.5	1.87	20.6	0.81	3/4-16
DCC94-12-12S	3/4-16	22.2	0.87	46.7	1.84	31.0	1.22	20.6	0.81	3/4-16
DCC94-14-14	7/8-14	25.4	1.00	52.3	2.06	65.0	2.56	23.8	0.94	7/8-14
DCC94-14-14D52.5	7/8-14	25.4	1.00	52.3	2.06	52.5	2.07	23.8	0.94	7/8-14
DCC94-14-14S	7/8-14	25.4	1.00	55.3	2.18	34.0	1.34	23.8	0.94	7/8-14
DCC94-17-17	1-1/16-12	31.8	1.25	67.0	2.64	95.0	3.74	28.6	1.12	1-1/16-12
DCC94-17-17D63.5	1-1/16-12	31.8	1.25	67.0	2.64	63.5	2.50	28.6	1.12	1-1/16-12
DCC94-17-17S	1-1/16-12	31.8	1.25	67.0	2.64	53.0	2.09	28.6	1.12	1-1/16-12
DCC94-21-21	1-5/16-12	38.1	1.50	78.1	3.07	107.0	4.21	35.0	1.38	1-5/16-12
DCC94-21-21S	1-5/16-12	38.1	1.50	78.1	3.07	70.0	2.76	35.0	1.38	1-5/16-12
DCC94-26-26	1-5/8-12	50.0	1.97	96.8	3.81	130.0	5.12	42.9	1.69	1-5/8-12
DCC94-26-26S	1-5/8-12	50.0	1.97	96.8	3.81	85.0	3.35	42.9	1.69	1-5/8-12
DCC94-30-30S	1-7/8-12	55.0	2.17	122.5	4.82	110.0	4.33	54.0	2.13	1-7/8-12